Product datasheet

Specifications



Actassi - patch panel - category 6 - UTP - 24-port - unloaded

ACTPP6U24NSSUN

Main

range of product	Actassi
Product or component type	Patch panel
Device presentation	Empty
Provided equipment	Without RJ45 connectors

Complementary

[In] rated current	1.5 A
Number of port	24 port of UTP
Product compatibility	standard 19" cabinet/rack
Communication network category	6 5e
Contact resistance	20 µOhm
Insulation resistance	>= 10 MOhm
Minimum number of matings	750 cycles
Number of rack unit	1U
Type of connector	S-110 keystone

Environment

Ambient air temperature for operation	-10…50 °C
Ambient air temperature for storage	-20…60 °C
Relative humidity	0…93 %
Standards	TIA/EIA-568-B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	12.5 cm
Package 1 Length	49.7 cm
Package 1 Weight	816.0 g

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**7 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**5 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Halogen free product**
PVC free	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**0**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**